

CLAIMS

1. Personal audio relay apparatus comprising:
a mobile telecommunications device for supporting a
5 telecommunications link and having at least one input;
a portable audio signal source device having at least one output; and
control means,
wherein said mobile telecommunication device and said audio signal
source are responsive to the control means to establish a signal path between
10 the at least one output of the audio signal source and the at least one input of
the telecommunications device to relay audio signals from the audio source
device over a telecommunications link.
2. The apparatus of claim 1 wherein said at least one output of the
15 audio signal source device provides audio signals in an analogue format and
said at least one input of the telecommunications device receives said signals
in the said analogue format.
3. The apparatus of claim 1 wherein said at least one output of the
20 audio signal source device provides audio signals in a digital format and said
at least one input of the telecommunications device receives said signals in
the said digital format.
4. The apparatus of claim 3 wherein said audio signal source device is
25 an MP3 player.
5. The apparatus of claim 1 wherein the said mobile
telecommunications device is a portable telephone.
- 30 6. The apparatus of claim 1 wherein the mobile telecommunications
and portable audio signal source devices are integrated.

09070297, 061131
TOTAL 2622080

with one of said mobile telecommunications device or said portable audio signal source and connectable to the other thereof.

5 8. The apparatus of claim 1 further comprising user operable input means by which the control means is operable under user command.

9. The apparatus of claim 1 wherein said control means establishes
said signal path when an audio signal is detected at the source device at least
10 one output.

10. The apparatus of claim 1 wherein the mobile telecommunications device is provided with an audio input transducer for generating an electrical output signal and said output signal is muted when said control means establishes said signal path.

11. A garment featuring the personal audio relay apparatus of claim 1.

12. The garment of claim 11 and further comprising an integrated
20 interconnect arrangement for connecting components of the personal audio
relay apparatus.